

ELECTRA 1007 BE

Product specification sheet

OPC (Optimum Phase Crossover)

- › Perfect staging.
- › High quality capacitors and inductors.
- › Focal binding post to offer high torque and excellent contact.

Rear laminar port

- › No air noise.
- › Very low distortion, no dynamic compression.
- › Foam bung for bass level setting.

Dedicated stand S 1007

- › 26" (60cm) height.
- › Sophisticated design.
- › Two finishes, satin black or lacquered black.
- › Loudspeaker fixing included.



Tweeter IAL

- › Pure Beryllium inverted dome tweeter.
- › IAL (Infinite Acoustic Loading) system.
- › Wide response to 40kHz.
- › Very low resonant frequency : 680Hz.
- › High efficiency : 95dB/W/m.

6-1/2" W cone mid-bass

- › 6-1/2" (165mm) W cone mid-bass
- › Patented sandwich composite design.
- › Outstanding stiffness and lightness

Advanced γ Structure

- › Massive structure of 2" (50mm) thick MDF.
- › No diffraction effect.
- › High inertia, no vibrations.

Removable grill for tweeter and midbass.

Features

- High technology line ;
- A pure Beryllium inverted dome for ultra wide band tweeter (1kHz to 40kHz) ;
- IAL (Infinite Acoustic Loading) system for optimal response ;
- Very low (2000Hz) frequency crossover for more detailed and dynamic midrange ;
- New generation woofer composite W sandwich cones ;
- New Advanced γ Structure for no diffraction effect ;
- Two finishing available Classic and Signature.

Technical specifications

Type	2-way bass-reflex bookshelf loudspeaker
Drivers	1" pure Beryllium IAL inverted dome tweeter 6-1/2" (165mm) W cone mid-bass
Frequency response	46Hz to 40kHz
Cut-off frequency (-6dB)	41Hz
Sensitivity (2.83V/1m)	89dB
Nominal impedance	8Ω
Minimum Impedance	3.9Ω at 200Hz
Max. power handling	90W
Crossover frequency	2000Hz
Dimensions (HxWxD)	15 ^{3/16} "x10 ^{3/8} "x10 ^{3/4} " (385x264x350mm)
Weight	33lbs (15kg)

